

Amendments To the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1 Claim 1 (currently amended): A switching network including rows and columns of
2 switches comprising:

3 a) a first stage of switches defining a first column of said switching
4 network having input lines and output lines and comprising m (n x k)
5 input switches, wherein m is an integer number, n is an integer
6 number representing the number of input lines and k is an integer
7 number representing the number of output lines;
8 b) a second stage of switches defining a second column of said switching
9 network comprising of m (k' x k') middle switches, k' is an integer
10 number representing the number of inputs and outputs; and
11 c) a third stage of switches defining a third column of said switching
12 network comprising of m (k x n) switches[,]; and
13 d) a plurality of modules, each module defining a row of the switching
14 network and including one input switch of the first stage of switches,
15 one middle switch of the second stage of switches, one output switch
16 of the third stage of switches.
17 wherein the modules of the plurality of modules are identical and k' is selected
18 such that $m * Q(k'/m) \geq k$ (where Q(x/y) denotes the quotient of dividing x by y)
19 to allow using m switches in the second stage.

1 Claim 2 (previously presented): A switching network comprising:
2 m identical modules, said module further comprising

3 a) an input stage comprising of a (n x k) switch wherein n is an
4 integer number representing the number of input lines and k is
5 an integer number representing the number of output lines;
6 b) a middle stage comprising of a (k' x k') switch, k' is an integer
7 number representing the number of inputs and outputs; and
8 c) an output stage comprising of a (k x n) switch

9 wherein k, k', and m satisfy $m^*Q(k'/m) \geq k$.

1 Claim 3 (currently amended): A method of constructing a switching network comprising:

- 2 a) using m identical modules, each module including switches, each switch
having input lines and output lines;
- 3 b) constructing said module from an input stage comprising of a (n x k)
switch, a middle stage comprising of a (k' x k') switch, an output stage
comprising of a (k x n) switch wherein n is an integer number
representing the number of input lines and k is an integer number
representing the number of output lines and k' is an integer number
representing the number of inputs and outputs; and
- 4 c) selecting k' such that $m^*Q(k'/m) \geq k$.

5 Claim 4 (currently amended): A module comprising:

- 6 a) an input stage comprising of a (n x k) switch wherein n is an integer
number representing the number of input lines and k is an integer
number representing the number of output lines;
- 7 b) a middle stage comprising of a (k' x k') switch, k' is an integer
number representing the number of inputs and outputs;
- 8 c) an output stage comprising of a (k x n) switch; and
wherein a switching network can be constructed using m of said modules, where
9 k, k', and m satisfy $m^*Q(k'/m) \geq k$.

10 Claim 5 (currently amended): A method of constructing a v(k, n, m) switching network
for values of m belonging to a non-empty set \mathcal{M} comprising:

- 1 a) using m identical modules, each module including switches, each switch having
input lines and output lines;
- 2 b) constructing said module from an input stage comprising of a (n x k) switch, a
middle stage comprising of a (k' x k') switch, an output stage comprising of a (k
x n) switch, wherein n is an integer number representing the number of input
lines and k is an integer number representing the number of output lines and k'
is an integer number representing the number of inputs and outputs; and
- 3 c) selecting k' such that $m^*Q(k'/m) \geq k$ for all values of m belonging to set \mathcal{M} .